

Application	Thin Brick	Thin Rock
Exterior Sheathing	2 Layers WRB LOXON Power Grab Adhesive Pointing Mortar Or 2 Layers WRB Metal Lath Scratch Coat Mortar Setting Bed Pointing Mortar	2 Layers WRB Metal Lath Scratch Coat Mortar Setting Bed Pointing Mortar
Exterior Concrete or Block	Power Wash or Sand Blast Scratch Coat Mortar Setting Bed Pointing Mortar Or Pressure Wash or Sand Blast Thin Set Pointing Mortar	Pressure Wash or Sand Blast Scratch Coat Mortar Setting Bed Joint Grout Or Pressure Wash or Sand Blast Thin Set Pointing Mortar
Interior Sheet Rock	Fiber Cement Backer Board Metal Lath Scratch Coat Mortar Setting Bed Pointing Mortar Or Fiber Cement Backer Board Thin Set Pointing Mortar Or Loxon Power Grab Adhesive Pointing Mortar Or Prime Sheet Rock w/Zinzer Power Grab Adhesive Pointing Mortar	Fiber Cement Backer Board Metal Lath Scratch Coat Mortar Setting Bed Pointing Mortar Or Fiber Cement Backer Board Thin Set Pointing Mortar

Notes:

1. WRB is a weather resistant barrier (i.e. Housewrap; Tyvec, or Felt)
2. Pointing Mortar: 1 bag mortar per 100 sq. ft.
3. Mortar Setting Bed: 2 bags mortar per 100 sq. ft.
4. Power Grab Adhesive: 20 sq. ft. per large tube (29 oz)